



OAK EGGSHELL

This single-strip oak floor from the Lux Collection features a misty white transparent stain, which allows distinctive gradations in the wood to come through. Four-sided micro-bevelling at the edging ensures a classic full plank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|---|---|----------------------|---------------------|---------------------------------|-------------|------------------------|
| Article Number | 151N51EKC4KW240 | Wood Species | Oak | Moisture | EN13183 | 7%±2% |
| EAN Code | 7393969047982 | Board | 1-strip | content | | |
| Surface treatment Design features | Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles. Microbevelled 4-sided, Brushed | Grading | Lively | Minimun Mean Density kg/m³ | | >500 kg/m ³ |
| | | Range | Kährs Original | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | | Collection | Lux Collection | Formaldehyde Emission | EN717-1 | E1 |
| | | Resandable | 2-3 times | | | |
| | | Natural/Stained | Stained | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Dimensions | 2420 x 151 x 15 mm | Brinell Value | 3,7 | Breaking EN1533 Strength N/mm² | NPD | |
| Weight per Package x | 17.85 kg | Joint | Woodloc® 5S | | | |
| Area per Package (m²) | 2.19 | Floor heating | Yes | Thermal | EN12664 | 0,14 W/mK |
| Area per pallet (m²) | 118.26 | Warranty | 30 years | Conductivity | | |
| Package info | Packages may contain start and stop boards. | Wear-layer material | Hardwood | Thermal Resistance R-Value | | .11 (m2K/W) |
| | | Wear-layer thickness | 3.5 mm | Biological Durability | EN350-2 | Class 1 |
| DETAIL DESCRIPTION | | Core material | Pine/Spruce/Alder | CARB2 | | Compliant |
| All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks | | Thickness | 15 mm | | | |
| | | Surface Colour | White | | | |
| | | Installation method | Floating, Glue-down | | | |

COLOUR CHANGE

Stained product - noticeable color change over time

will be present in all sizes and numbers.

















Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.